



SCANNED, # 16

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1 16(c))	92-20 =	72	X \$ 18.00 =	\$1296.00
	INDEPENDENT CLAIMS (37 CFR 1 16(b))	4-3 =	1	X \$ 80.00 =	\$80.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1 16(d))			\$270.00 =	\$0
				BASIC FEE (37 CFR 1 16(a))	\$710.00
			Total of above Calculations =		\$2086.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				0
	TOTAL =				\$2086.00

19. Small entity status

- a. ☐ A small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 2086.00 to cover the filing fee is enclosed.21. ☐ A check in the amount of \$ _____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED	
NAME	JACK M. ARNOLD
SIGNATURE	<i>Jack M. Arnold</i> Reg. No. 25,823
DATE	October 30, 2000

09-067

CORRESPONDENCE INFORMATION

APPLICATION INFORMATION

Total Drawing Sheets:: 35
Formal Drawings?: Yes
Application Type:: Utility
Docket Number:: 35.C14901
Secrecy Order in Parent Appl.?: No

Representative Customer Number:: 5514

1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Discussion**
 6. **Conclusion**
 7. **References**
 8. **Appendix**
 9. **Figure 1**
 10. **Figure 2**
 11. **Figure 3**
 12. **Figure 4**
 13. **Figure 5**
 14. **Figure 6**
 15. **Figure 7**
 16. **Figure 8**
 17. **Figure 9**
 18. **Figure 10**
 19. **Figure 11**
 20. **Figure 12**
 21. **Figure 13**
 22. **Figure 14**
 23. **Figure 15**
 24. **Figure 16**
 25. **Figure 17**
 26. **Figure 18**
 27. **Figure 19**
 28. **Figure 20**
 29. **Figure 21**
 30. **Figure 22**
 31. **Figure 23**
 32. **Figure 24**
 33. **Figure 25**
 34. **Figure 26**
 35. **Figure 27**
 36. **Figure 28**
 37. **Figure 29**
 38. **Figure 30**
 39. **Figure 31**
 40. **Figure 32**
 41. **Figure 33**
 42. **Figure 34**
 43. **Figure 35**
 44. **Figure 36**
 45. **Figure 37**
 46. **Figure 38**
 47. **Figure 39**
 48. **Figure 40**
 49. **Figure 41**
 50. **Figure 42**
 51. **Figure 43**
 52. **Figure 44**
 53. **Figure 45**
 54. **Figure 46**
 55. **Figure 47**
 56. **Figure 48**
 57. **Figure 49**
 58. **Figure 50**
 59. **Figure 51**
 60. **Figure 52**
 61. **Figure 53**
 62. **Figure 54**
 63. **Figure 55**
 64. **Figure 56**
 65. **Figure 57**
 66. **Figure 58**
 67. **Figure 59**
 68. **Figure 60**
 69. **Figure 61**
 70. **Figure 62**
 71. **Figure 63**
 72. **Figure 64**
 73. **Figure 65**
 74. **Figure 66**
 75. **Figure 67**
 76. **Figure 68**
 77. **Figure 69**
 78. **Figure 70**
 79. **Figure 71**
 80. **Figure 72**
 81. **Figure 73**
 82. **Figure 74**
 83. **Figure 75**
 84. **Figure 76**
 85. **Figure 77**
 86. **Figure 78**
 87. **Figure 79**
 88. **Figure 80**
 89. **Figure 81**
 90. **Figure 82**
 91. **Figure 83**
 92. **Figure 84**
 93. **Figure 85**
 94. **Figure 86**
 95. **Figure 87**
 96. **Figure 88**
 97. **Figure 89**
 98. **Figure 90**
 99. **Figure 91**
 100. **Figure 92**
 101. **Figure 93**
 102. **Figure 94**
 103. **Figure 95**
 104. **Figure 96**
 105. **Figure 97**
 106. **Figure 98**
 107. **Figure 99**
 108. **Figure 100**
 109. **Figure 101**
 110. **Figure 102**
 111. **Figure 103**
 112. **Figure 104**
 113. **Figure 105**
 114. **Figure 106**
 115. **Figure 107**
 116. **Figure 108**
 117. **Figure 109**
 118. **Figure 110**
 119. **Figure 111**
 120. **Figure 112**
 121. **Figure 113**
 122. **Figure 114**
 123. **Figure 115**
 124. **Figure 116**
 125. **Figure 117**
 126. **Figure 118**
 127. **Figure 119**
 128. **Figure 120**
 129. **Figure 121**
 130. **Figure 122**
 131. **Figure 123**
 132. **Figure 124**
 133. **Figure 125**
 134. **Figure 126**
 135. **Figure 127**
 136. **Figure 128**
 137. **Figure 129**
 138. **Figure 130**
 139. **Figure 131**
 140. **Figure 132**
 141. **Figure 133**
 142. **Figure 134**
 143. **Figure 135**
 144. **Figure 136**
 145. **Figure 137**
 146. **Figure 138**
 147. **Figure 139**
 148. **Figure 140**
 149. **Figure 141**
 150. **Figure 142**
 151. **Figure 143**
 152. **Figure 144**
 153. **Figure 145**
 154. **Figure 146**
 155. **Figure 147**
 156. **Figure 148**
 157. **Figure 149**
 158. **Figure 150**
 159. **Figure 151**
 160. **Figure 152**
 161. **Figure 153**
 162. **Figure 154**
 163. **Figure 155**
 164. **Figure 156**
 165. **Figure 157**
 166. **Figure 158**
 167. **Figure 159**
 168. **Figure 160**
 169. **Figure 161**
 170. **Figure 162**
 171. **Figure 163**
 172. **Figure 164**
 173. **Figure 165**
 174. **Figure 166**
 175. **Figure 167**
 176. **Figure 168**
 177. **Figure 169**
 178. **Figure 170**
 179. **Figure 171**
 180. **Figure 172**
 181. **Figure 173**
 182. **Figure 174**
 183. **Figure 175**
 184. **Figure 176**
 185. **Figure 177**
 186. **Figure 178**
 187. **Figure 179**
 188. **Figure 180**
 189. **Figure 181**
 190. **Figure 182**
 191. **Figure 183**
 192. **Figure 184**
 193. **Figure 185**
 194. **Figure 186**
 195. **Figure 187**
 196. **Figure 188**
 197. **Figure 189**
 198. **Figure 190**
 199. **Figure 191**
 200. **Figure 192**
 201. **Figure 193**
 202. **Figure 194**
 203. **Figure 195**
 204. **Figure 196**
 205. **Figure 197**
 206. **Figure 198**
 207. **Figure 199**
 208. **Figure 200**
 209. **Figure 201**
 210. **Figure 202**
 211. **Figure 203**
 212. **Figure 204**
 213. **Figure 205**
 214. **Figure 206**
 215. **Figure 207**
 216. **Figure 208**
 217. **Figure 209**

NY_MAIN 122560 v 1

[illegible]

Field of the Invention

10

15

20

25

simultaneously print the print jobs generated by, for instance, an application A suitable for preparing documents, an application B suitable for preparing charts or tables, an application C suitable for preparing drawings, etc., however, the "collective printing" function has been disadvantageously inferior in its maneuverability, because the "collective printing" function only serves to collect a plurality of print jobs together to one print job, and, because upon printing data, the data is outputted in regular order according to which the data is spooled for the collective printing in response to the instruction of collective printing, so that the user must spool the data on outputted pages. For instance, in the case where the user wishes to print data composed of a document, a drawing, a document, a table and a document each of which is written on one page, the user has inconveniently needed to prepare a first page by the application A and spool it, prepare a second page by the application B and spool it, prepare a third page again by the application A and spool it, prepare a fourth page by the application C and spool it and prepare a fifth page by the application A and spool it.

Further, in the case where the user wishes to see the preview of data collected together as one data to be printed, the user can see the preview provided by each application, however, it has been impossible for

the user to see the preview based on a plurality of print settings set by the printer driver.

Still further, in the case where the user wishes to put a plurality of files together and print them as one print job, when the user tries to carry out a designation of finishing relative to the print job thus obtained, there is no means for providing the designation of finishing relative thereto. There is undesirably provided no means having a preview function either. Therefore, unless the user prints the data, the user cannot disadvantageously understand how the data is actually printed and outputted by the printer.

Still further, in the case where the "collective printing" is employed to use a page layout function (N pages/sheet) in a device side, the same page layout processing can be carried out relative to a plurality of jobs, however, the print jobs cannot be combined together while a different layout is applied to each of the original print jobs.

As described above, the conventional "collective printing" only functions as a continuous printing, and therefore, one print job cannot be prepared by using a different layout for each page.

Further, as described above, according to the prior art, only one page layout can be provided for one job. Therefore, in the case where one job is formed for the collective printing, the user cannot designate

the page layout when the print jobs are previously
outputted from the applications for the collective
printing, that is to say, printing the print jobs in
one lot, so that the user has needed to select only one
5 page layout upon collective printing.

SUMMARY OF THE INVENTION

Thus, it is an object of the present invention to
provide an arrangement for combining together print
10 jobs respectively having print setting information.

Further, when one composed job is formed by
combining together a plurality of print jobs
respectively having the print setting information, if
the print jobs are respectively separately set for
15 printing operation, any mechanism will be needed for
unifying a plurality of settings. Accordingly, it is
another object of the present invention to provide an
arrangement by which a user can understand what is
changed to unify the settings upon automatic
20 unification.

Still further, it is a still another object of the
present invention to provide a function for managing
and editing functions for each job after a plurality of
print jobs are put together, for instance, a function
25 for rearranging a print order for each job irrespective
of an order in which the print jobs are printed and a
function for deleting the print jobs from a composed

5

5

10

15

20

25

and temporarily storing the print jobs; a composition
instructing unit for instructing a plurality of print
jobs corresponding to the different data to be printed
to be combined together so as to generate one composed
5 job; and a setting unifier for analyzing the print
setting information of a plurality of print jobs when
the composition instructing unit instructs the
plurality of print jobs to be combined together so as
to obtain one composed job, and generating print
10 setting information for the composed job by unifying
information which can be respectively merely set to one
print job.

Further, the setting unifier further includes a
recognizing unit for analyzing the print setting
15 information of a plurality of print jobs to be combined
together and recognizing to select whether the settings
are unified or the print jobs are not combined together
when information which can be set only to one print job
is mutually different.

20 Still further, the spooler converts the data to be
printed into the print jobs of intermediate code format
and temporarily stores the print jobs as page
description files for each page.

Still further, information for designating the
25 page description files laid out on a physical page is
added to the print setting information of the composed
job.

Still further, the above described print setting information is temporarily stored as a print setting file of each print job.

5 Still further, the information processor further comprises a preview display controller for controlling a preview based on the print setting information of the print jobs or the composed job to be displayed.

10 Still further, the information processor further comprises an order controller for operating a plurality of print jobs in the composed job to reshuffle the order of the print jobs.

15 Still further, the information processor further comprises a job cancelling unit for operating a plurality of print jobs in the composed job to cancel a specific print job.

Still further, the information processor further comprises a job divider for dividing the composed job into a plurality of print jobs before they are joined together.

20 Still further, the information processor further comprises a job duplicating unit for designating the print job or the composed job to prepare the duplication of the designated print job.

25 Still further, the print job or the composed job further includes a setting initializing unit for returning the intermediate code format as the base of the job to an initial state upon preparation of the

data based on the print setting information.

Still further, the information processor further comprises a page editing unit for cancelling a page designated relative to a logical page in the print job or the composed job.

Still further, the information processor further comprises a printing data generator for generating the printing data to be transmitted to the printing device on the basis of the data of the intermediate code format which is temporarily stored by a intermediate code converter.

Still further, the information processor further comprises a description instruction generator for converting the data of the intermediate code format temporarily stored by the intermediate code converter into a description instruction which can be interpreted by the description unit of an OS for outputting; and a print instruction allocator for sending the print instruction received through the description unit of the OS from the application to the intermediate data converter and sending the print instruction received through the description unit of the OS from the description instruction generator to the printing data generator.

In addition, the description instruction is a GDI function, the print instruction is a DDI function and the printing data is a printer language.

Furthermore, the information processor further comprises a layout unification instructing unit for instructing the layout information of the composed job to be unified and the composed job information generator unifies the layout information of the composed job by all physical pages when the layout unification instructing unit instructs the layout information to be unified.

Besides, the present invention can be realized by a method for controlling the image processor, a memory medium in which a program is stored or a computer program.

Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram for explaining the configuration of a print controller showing an embodiment of the present invention;

Fig. 2 is a block diagram showing a representative print system of a hostcomputer to which a printer is connected;

Fig. 3 is a block diagram showing the

configuration of the print system for temporarily spooling an intermediate code before a print instruction from an application is converted into a printer control command;

Fig. 4 is an explanatory view of the printer in the present invention;

Fig. 5 is a flowchart showing processings in a spooler 302;

Fig. 6 is a flowchart showing a print control in a
10 spool file manager 304;

Fig. 7 is a flowchart showing processings in a despooler 305;

Fig. 8 shows one example of a print setting screen;

```
15      Fig. 9 shows one example of a print spool setting
      screen;
```

Fig. 10 is a view showing one example of a data format delivered when the spool file manager 304 supplies a print request for a physical page to the despooler 305;

Fig. 11 is a view showing one example of a data format delivered when the spool file manager 304 supplies a print request for a physical page to the despooler 305;

25 Fig. 12 is a view showing one example of a data
format delivered when the spool file manager 304
supplies a print request for a physical page to the

despooler 305;

Fig. 13 is a view showing one example of a data format delivered when the spool file manager 304 supplies a print request for a physical page to the despooler 305;

Fig. 14 is a view showing one example of a data format delivered when the spool file manager 304 supplies a print request for a physical page to the despooler 305;

Fig. 15 is a flowchart showing setting change processes in a setting change editor 307;

Fig. 16 shows one example of a screen displaying a print job list spooled in the spool file manager 304;

Fig. 17 shows one example of a screen of a previewer 306;

Fig. 18 shows one example of a screen of the setting change editor 307;

Fig. 19 is a flowchart showing the operation of a user when the print jobs are spooled in the spool file manager 304 as shown in Fig. 16;

Fig. 20 is a flowchart showing the operation of the user upon composing the jobs together;

Fig. 21 is a conceptual view for explaining the unification and rounding off of settings when a plurality of documents are combined together;

Fig. 22 shows one example of a user interface for selecting a plurality of documents to be combined

Fig. 23 shows one example of the user interface for requesting for the recognition of the unification and rounding off of the settings upon combination of the documents;

Fig. 25 shows one example of a recognition message when the jobs are decomposed;

Fig. 26 shows one example of a classification showing the settings which are unified and the settings which are not unified upon unification and rounding off the settings when the jobs are composed together;

Fig. 27 shows one example of a data structure when the spool file manager 304 manages a plurality of print jobs;

Fig. 28 shows one example of a data structure when the spool file manager 304 manages a plurality of print jobs and a plurality of composed jobs;

Fig. 29 shows one example of the inner structure of an intermediate file;

Fig. 30 shows one example of a screen for editing the composed job;

Figs. 31A and 31B show one example of data processings such as reshuffling the order of the

5

10

15

20

25

Fig. 37 shows one example of a processing flow for preparing and changing a setting file for outputting a job;

Fig. 38 shows one example of a processing flow for calculating physical page information;

Fig. 39 shows one example of a processing flow for obtaining physical page setting information;

Fig. 40 shows one example of a screen of the setting change editor 307; and

Fig. 41 shows one example of a screen of the setting change editor 307.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now, preferred embodiments to which the present invention is applicable will be described below.

Fig. 1 is a block diagram for explaining the configuration of a printer control system showing an embodiment of the present invention. The present invention is applicable to any printer control system by which the functions of the present invention can be executed, such as a system composed of a single device or a plurality of devices, a system which is connected through a network such as LAN, WAN, etc. to perform various processings.

In Fig. 1, a host computer 3000 is provided with a CPU 101 for executing a document processing in which graphic forms, images, characters, tables (including table calculations), etc. are mixed on the basis of a document processing program or the like stored in the ROM for program of a ROM 103 or an external memory 111. The CPU 101 generally controls respective devices connected to a system bus 104. In the ROM for program of the ROM 103 or the external memory 111, an operating system program (called an OS, hereinafter) as a control program of the CPU 101 is stored. In a ROM for font of the ROM 103 or the external memory 111, font data employed for a document processing is stored. In a ROM for data of the ROM 103 or the external memory 111, various kinds of data used for carrying out the

A keyboard controller (KBC) 105 controls a key input from a keyboard 109 or a pointing device not shown. A CRT controller (CRTC) 106 controls the display of a CRT display (CRT) 110. Reference numeral 107 designates a disk controller (DKC) and controls an access to the external memory 111 such as a hard disk (HD), a floppy disk (FD), etc. for storing a boot program, various kinds of applications, font data, a user file, an edit file, a printer control command generating program (called a printer driver, hereinafter), etc. A printer controller (PRTC) 108 is connected to a printer 1500 through a two-way interface 121 to control a communication with the printer 1500.

The CPU 101 expands (rasterizes), for example, an outline font to display information RAM set on the RAM 102 to enable WYSIWYG on the CRT 110. Further, the CPU 101 opens various kinds of windows registered on the basis of commands instructed by a mouse cursor not shown on the CRT 110 to perform a variety of data processings. When a user performs a printing operation, the user opens a window concerning a setting of print to perform the setting of the printer or the setting of a print processing method relative to the printer driver including the selection of a print mode.

The printer 1500 is controlled by a CPU 112. The

printer CPU 112 outputs an image signal as output information to a printer engine 117 connected to a system bus 115 on the basis of a control program stored in the ROM for program of a ROM 113 or a control program stored in an external memory 114 or the like.

Further, in the program ROM of the ROM 113, the control program of the CPU 112 is stored. In the ROM for font of the ROM 113, font data or the like for generating the output information is stored. In the ROM for data of the ROM 113 is stored information utilized on the host computer, in the case of a printer having no external memory 114 such as a hard disk.

The CPU 112 can communicate with the host computer through an input unit 118 so as to inform the host computer 3000 of the information or the like in the printer. A RAM 119 is a RAM which functions as the main memory or the work area of the CPU 112 and is designed to expand a memory capacity by an option RAM connected to an extended port not shown. The RAM 119 is employed for an output information expanded area, an environmental data stored area, an NVRAM, etc. The access of the above described external memory 114 such as the hard disk (HD), an IC card, etc. is controlled by a memory controller (MC) 120. The external memory 114 is connected as an option to store font data, an emulation program, form data, etc. Reference numeral 1501 denotes an operation panel on which switches for

operation and an LED display devices or the like are arranged.

The number of the above described external memory 114 is not limited to one and a plurality of external memories may be provided. A plurality of external memories, in which option cards as well as an integrated font and programs which can interpret printer control languages different in their language system are stored, may be connected together. Further, an NVRAM not shown may be provided so as to store printer mode setting information from the operation panel 1501.

Fig. 2 is a block diagram showing a representative printing process in the host computer to which a printing device such as the printer is directly connected or via a network. An application 201, a graphic engine 202, a printer driver 203 and a system spooler 204 are program modules with which the RAM 102 is loaded and which are executed by the OS or modules using its module, when they exist as files stored in the external memory 111 and are executed. Further, the application 201 and the printer driver 203 can be added to the HD of the external memory 111 via the FD of the external memory 111, a CD-ROM not shown or a network not shown. The application 201 stored in the external memory 111 with which the RAM 102 is loaded is executed by the RAM 102. When the printing operation is carried

out on the printer 1500 from the application 201, an output (image description) is performed by using the graphic engine 202 with which the RAM 102 is similarly loaded to be executable.

5 The graphic engine 202 similarly loads the RAM 102 with the printer driver 203 prepared for each printing device from the external memory 111 and sets the output of the application 201 to the printer driver 203.

10 Then, the graphic engine 202 converts a GDI (Graphic Device Interface) function received from the application 201 into a DDI (Device Driver Interface) function and outputs the DDI function to the printer driver 203. The printer driver 203 converts the DDI function received from the graphic engine 202 into a
15 control command, for instance, a PDL (Page Description Language) which can be recognized by the printer. The printer control command thus obtained is adapted to be outputted to the printer 1500 as printing data through the interface 121 via the system spooler 204 with which
20 the RAM 102 is loaded by the OS.

 The print system according to the present embodiment comprises a configuration in which the printing data from the application is temporarily spooled by intermediate code data as shown in Fig. 3 in
25 addition to the print system having the host computer and the printer as shown in Fig. 2.

 A system shown in Fig. 3 is formed by extending

the system shown in Fig. 2 and is configured to temporarily generate a spool file 303 composed of the intermediate code when a print instruction is sent to the printer driver 203 from the graphic engine 202. In the system shown in Fig. 2, the application 201 is released from the printing process when the printer driver 203 completely converts all the print instructions from the graphic engine 202 into the control commands of the printer. On the other hand, in the system shown in Fig. 3, the application is released from the printing process when a spooler 302 converts all the print instructions into the intermediate code data and outputs the intermediate code data to the spool file 303. The latter ordinarily takes a shorter time than the former. Further, in the system shown in Fig. 3, the contents of the spool file 303 can be processed. Thus, can be realized functions which are not provided in the application, such as enlargement/reduction, reduction and print of a plurality of pages to one page, etc. relative to the printing data from the application.

For achieving these objects, the system has been adapted to be extended in such a manner that the printing data is spooled by the intermediate code data as shown in Fig. 3 as compared with the system shown in Fig. 2. In order to process the printing data, a setting is ordinarily carried out from a window

provided by the printer driver 203. The printer driver 203 stores the contents of the setting on the RAM 102 or in the external memory 111.

Now, the detail of the print system shown in Fig. 3 will be described below. As shown in Fig. 3, according to the extended processing system, a dispatcher 301 receives the DDI function as the print instruction from the graphic engine 202. In the case where the print instruction (DDI function) that the dispatcher 301 receives from the graphic engine 202 is based on the print instruction (GDI function) sent to the graphic engine 202 from the application 201, the dispatcher 301 loads the RAM 102 with the spooler 302 stored in the external memory 111 and transmits the instruction (DDI function) not to the printer driver 203 but to the spooler 302.

The spooler 302 analyzes the received print instruction, converts it into the intermediate code for each page and outputs the intermediate code to the spool file 303. The spool file of the intermediate code stored for each page is called a page description file (PDF). The spooler 302 obtains from the printer driver 203 the processed settings of the printing data set to the printer driver 203 (Nup, duplex printing, stapling, color/monochrome designations, etc.) and stores them in the spool file 303 as files for each job. The setting file stored for each job is called a

10

15

25

25

graphic engine 202 corresponds to a print instruction based on a print instruction (GDI function) supplied to the graphic engine 202 from the despooler 305, the dispatcher 301 sends the print instruction not to the spooler 302 but to the printer driver 203.

The printer driver 203 generates a printer control command composed of a page description language or the like on the basis of the DDI function got from the graphic engine 202, and outputs the command to the printer 1500 via the system spooler 204.

Further, referring to Fig. 3, there is shown an example in which a previewer 306 and a setting change editor 307 are added to the extending system explained so far so that a print can be previewed, a print setting can be changed, and a plurality of jobs can be composed together.

In order to preview the print, change the print setting and compose a plurality of jobs together, the user needs to first designate "store" in a pull-down menu as means for "designating an output destination" in the property of the printer driver shown in Fig. 9. When the user wishes to see only the preview, the user can select a "preview" as the designation of the output destination.

Contents set in the property of the printer driver as described above are stored as setting files in a structure body (called DEVMODE, in Windows OS) provided

[illegible][illegible][illegible]

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

edit" for changing the print setting (layout setting, finishing setting, etc.) of a single job or the composed job, "move to the first" for moving a job to the top in print order, "move faster by one" for moving a job faster by one in print order, "move slower by one" for moving a job slower by one in print order and "move to the last" for moving a job to the last in print order.

When the preview of a single job or the composed job is designated on the window screen (see Fig. 16) of the spool file manager, the RAM 102 is loaded with the previewer 306 stored in the external memory 111 to instruct the previewer306 to execute the preview processing of the job of the intermediate code described on the spool file 303.

The previewer 306 sequentially reads the page description files (PDF) of the intermediate code contained in the spool file 303, processes them in accordance with the contents of the process setting information included in the job setting file (SDF) stored in the spool file 303 and outputs the GDI function to the graphic engine 202. Then, the graphic engine 202 outputs description data to a client area of itself, so that the data can be outputted onto the screen.

The graphic engine 202 can perform a suitable rendering depending on a designated output destination.

Accordingly, there can be realized a method in which the previewer 306 processes the intermediate codes included in the spool file 303 in accordance with the contents of the process setting contained in the spool file 303 and outputs the data thus obtained by employing the graphic engine 202, like the despooler 305. As described above, the process setting set by the printer driver is stored in the spool file 303 as the job setting file and the data of the page description file is processed on the basis of the job setting file and the processed data is outputted. Thus, can be provided for the user a print preview, as to how actual description data is printed, further print previews near those outputted by the printer respectively according to the cases where Nup (N logical pages are reduced, arranged and printed on one physical page) is designated, a duplex side print is designated, a binding print is designated and a stamp is designated. A preview function of an application software for preparing a document in the prior art serves to basically describe an image on the basis of the page setting of the application, so that the print setting of a printer driver is not effected and the user cannot recognize a preview whose print is actually outputted.

As described above, the preview processing is carried out, so that the large preview of the process

setting of print included in the spool file 303 is displayed on a screen by the previewer 306 as illustrated in Fig. 17. After that, the previewer 306 is closed in accordance with the non-display
5 instruction of the user to shift a control to the window screen (see Fig. 16) of the spool file manager.

Then, when the user prints the data in accordance with the contents displayed by the previewer 306, the user designates the "print" or the "print
10 conservatively" on the spool file manager 304 to supply a print request. In the print request, the page description file is processed by the despooler 305 on the basis of the job setting file to generate the GDI function, the GDI function is transmitted to the
15 graphic engine 202 and the print instruction is sent to the printer driver 203 via the dispatcher 301 to perform the printing operation.

Now, a setting change will be described by using the setting change editor 307.

20 A method for realizing the setting change can be set to a job to which the "store" is designated in Fig. 9 like the preview. The spool file manager 304 is popped up in accordance with a similar flow so that the spooled jobs are listed and displayed. On the window
25 screen (see Fig. 16) of the spool file manager, when the "job edit" is designated and the setting change is instructed, the RAM 102 is loaded with the setting

5 The setting change editor 307 obtains the job
setting file of a job to which the "job edit" is
designated from the spool file 303 to change the
default values of the job setting screen shown in Fig.
18 on the basis of the setting items designated in the
0 job setting file. Referring to an example shown in
Fig. 18, in the job setting file of the job to which
the "job edit" is designated, the number of copies:
one, a printing method: a single side printing,
stapling: no, layout: one page/sheet, etc. are
5 designated.

20 setting file stored in the spool file 303 and the
 processed file is outputted to its client area by using
 the graphic engine 202, so that a small preview on the
 screen shown in Fig. 18 can be outputted.

Further, the contents of the process setting included in the job setting file stored in the spool file 303 can be changed and corrected therein. At that time, items which can be set by the printer driver 203

5
10

15
20

25

202 and the print instruction is sent to the printer driver 203 via the dispatcher 301 to perform the printing operation.

Further, on the window screen (see Fig. 16) of the spool file manager, it is possible to designate that a plurality of jobs are composed together to print them as one print job. The above designation can be executed for the job to the output destination of which the "store" is designated in the property of the printer driver shown in Fig. 9 similarly to the preview and the setting change.

When the user combines the print jobs together, the user initially accesses the printer driver 203 from the application 201 to select the store on the user interface as shown in Fig. 9. As described above, the print jobs are stored in the spool file 303 in accordance with this selection and the window screen (see Fig. 16) of the spool file manager is popped up as illustrated in Fig. 16. The list of the spooled jobs is displayed on the window of the spool file manager. The same operation is carried out from the application 201, so that the list of a plurality of jobs is displayed on the spool file manager 304.

Here, when the plurality of jobs are selected and the "composition" is designated, the RAM 102 is loaded with the setting change editor 307 stored in the external memory 111 to instruct the setting change

editor 307 to display the process setting of a first job or a default on the list. Then, a composition setting screen as shown in Fig. 18 is displayed. Here, although the setting change editor 307 is used as the composition setting screen, it is to be understood that another module may be employed.

The setting change editor 307 processes the page description file of the intermediate code included in the spool file 303 on the basis of the contents of the process setting included in the job setting information stored in the spool file 303, and outputs the processed file to its own client area by employing the graphic engine 202 relative to all the jobs designated as the composed jobs to output the processed file on the screen. At that time, the small previews of all the jobs selected in a preview area shown in Fig. 18 can be seen. Further, when the composed job is formed, setting files for outputting jobs in which the job setting files of respective single jobs are extended are formed. The setting file for outputting the job is also formed when the job is edited. One setting file is generated for one job. In the case of one composed job, one setting file is also formed.

The respective jobs can be displayed on the basis of the process setting before they are composed together. The process settings of the jobs may be changed and corrected to process settings for

unification so as to display the jobs as the composed job. At that time, the items which can be set by the printer driver 203 may be provided in the user interface on the setting change editor 307 or the user interface of the printer driver 203 itself may be accessed.

As for the composed job and the changed items, the changes thereof are verified in accordance with the verification requests on the setting change editor 307, as mentioned above, to shift a control to the spool file manager 304. As a result of these operations, a plurality of previously selected jobs are displayed as one composed job on the window of the spool file manager.

Then, if the user performs a printing operation in accordance with the contents of the setting change like the recognition in the previewer 306, the user supplies a print request on the spool file manager 304. The print request is transmitted to the graphic engine 202 and sent to the printer driver 203 via the dispatcher 301 to execute the printing operation.

Fig. 4 is a sectional view of a color laser printer having a duplex side printing function as one example of the printer 1500.

This printer is adapted to form an electrostatic latent image by scanning a photosensitive drum 15 by a polygon mirror 31 through a laser beam modulated by

image data for each color obtained on the basis of
printing data inputted from the host computer 3000.

The electrostatic latent image is developed with toner
to obtain a visible image, which is subjected to a

5 multiple transfer of all colors to an intermediate
transfer body 9 to form a color visible image. Then,
the color visible image is transferred to a
transferring material 2 to fix the color visible image
thereon. An image forming part which carries out the
10 above described control comprises a primary charging
part including a drum unit having the photosensitive
drum 15 and a contact charging roller 17, a cleaning
part, a developing part, the intermediate transfer body
9, a sheet cassette 1, a sheet feeding part including
15 various kinds of rollers 3, 4, 5 and 7, a transfer part
including a transfer roller 10 and a fixing part 25.

The drum unit 13 comprises the photosensitive drum
(photosensitive body) 15 and a cleaner container 14
having a cleaning mechanism serving as the holder of
20 the photosensitive drum 15 which are integrally formed.
The drum unit 13 is attachably and detachably supported
by a printer main body and easily replaced by another
drum unit to meet the life of the photosensitive drum
15. The photosensitive drum 15 is configured by
25 applying an organic photoconductive layer to the outer
periphery of an aluminium cylinder and rotatably
supported by the cleaner container 14. The

photosensitive drum 15 is rotated by transmitting the driving force of a driving motor not shown thereto. The driving motor rotates the photosensitive drum 15 counterclockwise in accordance with an image forming operation. The surface of the photosensitive drum 15 is selectively exposed to form an electrostatic latent image. In a scanner part 30, the modulated laser beam is reflected by the polygon mirror rotating in synchronization with the horizontal synchronizing signal of an image signal by a motor 31a and the reflected beam is applied to the photosensitive drum through a lens 32 and a reflector 33.

A developing part comprises three color developing devices 20Y, 20M and 20C for developing yellow (Y), magenta (M) and cyan (C) and one black developing device 21B for developing black (B) in order to visualize the above described electrostatic latent image. The color developing devices 20Y, 20M and 20C and the black developing device 21B are respectively provided with sleeps 20YS, 20MS, 20CS and 21BS and application blades 20YB, 20MB, 20CB and 21BB in contact with the respective outer peripheries of these sleeps 20YS, 20MS, 20CS and 21BS. Further, the three color developing devices 20Y, 20M and 20C are provided with application rollers 20YR, 20MR and 20CR.

The black developing device 21B is detachably attached to the printer main body. The color

The sleep 21BS of the black developing device 21B is arranged with a very small clearance of, for instance, about 300 μm from the photosensitive drum 15. The black developing device 21B carries toner by a feeding member incorporated in the developer and applies an electric charge to the toner by a frictional electrification so as to apply the toner to the outer periphery of the sleep 21BS rotating clockwise by the application blade 21BB. A developing bias is applied to the sleep 21BS so that a developing operation is carried out to the photosensitive drum 15 in accordance with the electrostatic latent image to form a visible image of the black toner on the photosensitive drum 15.

At the time of forming a color image, the developing rotor 23 rotates for each rotation of the

intermediate transfer body 9 and developing processes are carried out in regular order of the yellow developing device 20Y, the magenta developing device 20M, the cyan developing device 20C and the black developing device 21B. The intermediate transfer body 9 rotates four times so that the visible images composed of respective toners of yellow, magenta, cyan and black are sequentially formed. As a result, a full color visible image is formed on the intermediate transfer body 9.

The intermediate transfer body 9 is adapted to come into contact with the photosensitive drum 15 and rotate together with the photosensitive drum 15, and rotates clockwise upon formation of a color image and receives the multiple transfer of the visible image four times from the photosensitive drum 15. Further, during the image formation, the transfer roller 10 comes into contact with the intermediate transfer body 9 so that the intermediate transfer body 9 simultaneously performs the multiple transfer of the color visible image there onto the transfer material 2. On the outer periphery of the intermediate transfer body, are arranged a TOP sensor 9a and an RS sensor 9b for detecting positions concerning the rotating direction of the intermediate transfer body 9 and a density sensor 9c for detecting the density of a toner image transferred to the intermediate transfer body 9.

The transfer roller 10 is provided with a transfer charger supported so as to be engaged with and disengaged from the photosensitive drum 15 and is configured by winding an intermediate resistance foaming elastic body on a metal shaft.

While the multiple transfer of the color visible image is carried out on the intermediate transfer body 9, the transfer roller 10 is, as shown by a solid line in Fig. 4, separated below from the body 9 so as not to disturb the color visible image. Then, after the four color visible image is formed on the intermediate transfer body 9, the transfer roller 10 is located at an upper position shown by a dotted line in Fig. 4 by a cam member (not shown) to a timing for transferring the color visible image to the transfer material 2. Thus, the transfer roller 10 comes into contact with the intermediate transfer body 9 under prescribed pressure through the transfer material 2 and applies a bias voltage to the intermediate transfer body 9 to transfer the color visible image on the intermediate transfer body 9 to the transfer material 2.

The fixing part 25 serves to fix the transferred color visible image to the transfer material while conveying the transfer material 2. The fixing part 25 is provided with a fixing roller 26 for heating the transfer material 2 and a pressing roller 27 for allowing the transfer material 2 to come into contact

with the fixing roller 26 under pressure. The fixing roller 26 and the pressing roller 27 are formed in hollow shapes and respectively have heaters 28 and 29 incorporated therein. In other words, the transfer material 2 holding the color visible image is conveyed by the fixing roller 26 and the pressing roller 27 and is subjected to heat and pressure to have the toner fixed on its surface.

The transfer material 2 to which the visible image is fixed is discharged to a sheet discharging part 37 by discharging rollers 34, 35 and 36 to finish the image forming operation.

The cleaning means serves to remove the toner remaining on the photosensitive drum 15 and the intermediate transfer body 9. Waste toner produced after the visible image with toner formed on the photosensitive drum 15 is transferred to the intermediate transfer body 9 or waste toner produced after the four color visible image formed on the intermediate transfer body 9 is transferred to the transfer material 2 are stored in the cleaner container 14.

The printed transfer material (recording sheet) 2 is taken out by a sheet feeding roller 3 from a sheet feeding tray 1, sandwiched in and conveyed between the intermediate transfer body 9 and the transfer roller 10 to record a color toner image thereon and passes the

fixing part 25 to fix the toner image thereto. In the case of a single side printing, a guide 38 forms a conveying passage to guide the recording sheet to the upper sheet discharging part. As compared with the above, in the case of a duplex side printing, the guide 38 forms a path to guide the recording sheet to a lower duplex side unit.

The recording sheet guided to the duplex side unit is temporarily fed to the lower part (conveying passage shown by a two-dot chain line) of the tray 1 by a conveying roller 40, and then conveyed in a reverse direction and fed to a duplex side tray 39. On the duplex side tray 39, the front surface and the back surface of the sheet are reverse to those of the sheet which is mounted on the sheet feeding tray 1 and the head and the last of the sheet in a conveying direction are reverse to those of the sheet mounted on the sheet feeding tray 1. The toner image is transferred and fixed again to the sheet under this condition, so that the duplex side printing can be realized.

Fig. 5 shows a flowchart showing the processes of storing steps for each page in the generation of the spool file 303 in the spooler 302.

Initially, in step 501, the spooler 302 receives a print request through the graphic engine 202 from the application. In the application, a dialogue for inputting a print setting as shown in Fig. 8 is

displayed and the print setting inputted from the
dialogue is delivered to the spooler 303 from the
printer driver. In the setting input dialogue shown in
Fig. 8, a setting item or the like for determining the
5 number of logical pages laid out in one physical page
as shown by reference numeral 801 is included.

In step 502, the spooler 302 decides whether or
not the received print request is a job start request.
When the spooler 302 decides that the print request is
10 the job start request in step 502, spooler advances to
step 503 to prepare the spool file 303 for temporarily
store intermediate data. Then, in step 504, the
spooler 302 informs the spool file manager 304 of the
progress of the printing process. In next step 505,
15 the page counter of the spooler 302 is initialized to
1. Here, the pool file manager 304 reads from the
spool file 303 and stores the information or the
process setting or the like of a job whose printing
operation is started.

20 On the other hand, in step 502, when the spooler
302 decides that the print request is not a job start
request, the spooler 302 advances to step 506.

In step 506, the spooler 302 decides whether or
not the received request is a job end request. When
25 the spooler 302 decides that the received request is
not the job end request, the spooler 302 advances to
step 507 to decide whether or not the received request

001201 62266960

5 Then, the spooler 304 increments a page number counter to close the page description file in which the intermediate code is stored and prepare a next page description file.

10

15

20

25

5

10

15

20

25

5

10

15

20

25

Then, in step 608, information such as a logical page number, the physical page number thereof, etc. which constitute a physical page to be printed is

stored in the setting file for outputting a job (a file including physical page information) in a form shown in Fig. 10 and the despooler 305 is informed of the addition of physical page information corresponding to one physical page. After that, the spool file manager 304 returns to step 601 to wait for a next notice. In the present embodiment, when the logical pages which constitute one page of printing data, that is to say, one physical page are spooled, the printing process can be executed even when the spool process of the print job is not completely finished.

On the other hand, in step 604, when the progress notice is not the print end notice of one logical page from the spooler 302, the spool file manager 304 advances to step 609 to decide whether or not the progress notice is the job end notice from the spooler 302 which is sent to the spool file manager 304 from the spooler in step 512. Here, when a replay is affirmative, the spool file manager 304 moves to the above described step 606. On the other hand, when a reply is negative, the spool file manager 304 proceeds to step 610 to decide whether or not the received notice is a print end notice of one physical page from

the despooler 305. Here, when the received notice is the print end notice of one physical page, the spool file manager 304 proceeds to step 612 to decide whether or not the print of the modification setting is

5 completely finished. When the printing process is finished, the spool file manager 304 advances to step 612 to inform the despooler 305 of the end of printing.

On the other hand, when the spool file manager 304 decides that the print of the modification setting is not finished, the spool file manager moves to step 606.

10 In the despooler 305 according to the present embodiment, it is assumed that the number of one physical page is a unit for executing the print process. Further, in step 608, information required

15 for performing the print process of one physical page is stored one by one in a file so as to be reused.

When the information does not need to be reused, a package system, may be provided, in which a high speed medium such as a common memory is used to successively
20 overwrite information thereon for each physical page so that speed and resources can be saved. Further, in the case where the progress of spooling is faster than that of despooling or in the case where a despooling process is started after all pages are spooled, the spool file
25 manager 304 does not inform the despooler 305 of the pages which can be printed for each physical page in step 608, and can save the number of notices by

informing the despooler of the contents of a notice that a plurality of physical pages or all physical pages can be printed in accordance with the progress of the despooling side.

5 In step 610, when the spool file manager 304 decides that the received notice is not the print end notice of one physical page from the despooler 305, the spool file manager 304 advances to step 613 to decide whether or not the notice is a print end notice from
10 the despooler 305. When it is decided that the notice is the print end notice from the despooler 305, the spool file manager 304 advances to step 614 to delete a corresponding description file of the spool file 303 and finish the processes. On the other hand, when the
15 notice is not the print end notice from the despooler 305, the spool file manager 304 proceeds to step 615 to perform other ordinary processes and wait for a next notice.

20 Fig. 7 is a flowchart showing the detail of the print data generating process in the despooler 305.

 The despooler 305 reads out necessary information (page description files and job setting files) from the spool file 303 in accordance with a print request from the spool file manager 304 to generating printing data.
25 The generated printing data is transferred to the printer in accordance with the method explained with reference to Fig. 3.

For generating the printing data, in step 701, the despooler 305 first inputs a notice from the spool file manager 304. In next step 702, the despooler 305 decides whether or not the inputted notice is the job end notice. When the inputted notice is the job end notice, the despooler 305 advances to step 703 to raise an end flag and move to step 705. On the other hand, in step 702, when the notice is not the job end notice, the despooler 305 advances to step 704 to decide whether or not the print start request of one physical page in step 608 is notified to the despooler. In step 704, when the despooler 305 decides that the notice is not the print start request, the despooler 305 advances to step 710 to carry out other error processes, return to step 701 and wait for a next notice. On the other hand, in step 704, when the despooler 305 decides that the notice is the print start request of one physical page, the despooler 305 advances to step 705 to store the ID of the physical page to be printed which the despooler receives the notice in step 704. In the next step 706, the despooler 305 decides whether or not the print processes of all the pages of the ID of the physical page stored in step 705 are completed. Here, when the processes of all the physical pages are completed, the despooler 305 advances to step 707 to decide whether or not the end flag in step 703 is raised. When the end flag is raised, the despooler 305

decides that the print process of the job is finished
and sends a notice of the end of processes to the spool
file manager 304 to finish the processes. In step 707,
when it is decided that the end flag is not raised, the
5 despooler 305 returns to the step 701 to wait for a
next notice. On the other hand, in step 706, when the
despooler 305 decides that there remain physical pages
to be printed, the despooler advances to step 708,
sequentially read IDs of physical pages to be processed
10 from the stored physical page IDs, read information
necessary for generating the printing data of the
physical pages corresponding to the read physical page
IDs and execute the print process. The print process
is performed by converting a print request instruction
15 stored in the spool file 303 into a format (GDI
function) which can be recognized by the graphic engine
202 in the despooler 305 and transferring the format.
As for the process setting or the modification setting
(called it N page printing, hereinafter) in which a
20 plurality of logical pages are laid out on one physical
page. The conversion is executed by considering a
reduced arrangement in step 708. When the required
print process is finished, the despooler 305 notifies
the spool file manager 304 of the end of print data
25 generation of one physical page in next step 709.
Then, the despooler 305 returns to the step 706 to
repeat the processes up to the print process for all

the physical page IDs to be printed which are stored in step 705.

As described above, a flow of the print processes include the dispatcher 301, the spooler 302, the spool file manager 304 and the despooler 305. According to the processes mentioned above, since the application 201 is released from the print process when the spooler 302 generates the intermediate code and stores it in the spool file 303, the former may take time shorter than a case in which the intermediate code is directly outputted to the printer driver 203. Further, since the intermediate code is temporarily stored in the spool file 303 as an intermediate file (page description file, job setting file) based on the print setting of the printer driver, a print preview to be actually printed can be recognized by the user or the print jobs generated by a plurality of applications can be combined together or rearranged. When the print setting is changed, the user can change the print setting without starting the application again to print.

In the print process using the spooler 302, when the print request is supplied to the graphic engine 202, the job output setting file is generated by the despooler 305. In the case where the previews or the jobs are combined together, the job output setting file is also generated. The job output setting file is, in

the case of a single job, equivalent to the job setting file. In the case of the composed job, the output setting file is generated on the basis of the setting information of a plurality of jobs. Now, the job output setting file will be described below.

Fig. 10 shows an example of the job output setting file in which information constituting the physical pages to be printed generated by the spool file manager 304 is stored in step 608. A field 1001 designates an ID for identifying a job which can be stored in the name of a file or a common memory for storing the information in question. A field 1002 designates job setting information. In the job setting information, is included information which can be necessarily set to only one job such as the designation of a structure body required for starting the print process of a job relative to the graphic engine 202 and the N page printing, the designation of an additional description such as a page frame, the finishing designation such as the number of copies, stapling, etc. In the job setting information 1002, there is stored only information required for the functions for the jobs. A field 1003 designates the number of physical pages of the job. After this field, the physical page information of the number shown in the field 1003 is stored. Since the present embodiment utilizes a system for notifying the user of the number of physical pages

to be printed, this field may not be required for operation. The physical page information of the number shown in the field 1003 is stored from a field 1004 to the last field. The physical page information will be described by referring to Fig. 12.

Fig. 11 shows one example of the job setting information shown in the field 1002 shown in Fig. 10. A field 1101 designates the number of all physical pages. A field 1102 designates the number of all logical pages. The fields 1101 and 1102 are added to the printing data and employed when a page number is printed as additional information. While the printing operation is continued, both the fields designate provisional values, or the spool manager 304 postpones the preparation of physical page information capable of being printed until the printing operation is finished. A field 1103 designates copy number information for designating what number of copies of the print job are printed. A field 1104 designates whether or not the print job is printed for each copy when a plurality of copies are printed in the field 1103. A field 1104 designates finishing information such as stapling, punching, folding in a Z-shape, etc. When a finisher is provided externally or in the printer main body, the finishing information is designated. A field 1106 indicates additional print information, and a decoration such as a page frame, additional information

such as date, and information added to a job such as a user name, a page number, water mark print, etc. are stored. As functions increase, the number of fields included in the job setting information also increases.

5 For example, when a duplex side printing can be carried out, a field for storing the designation of the duplex side printing is added thereto.

Fig. 12 shows one example of the physical page information shown in the field 1004 in Fig. 10. A
10 first field 1201 denotes physical page numbers which are values used when a print order is controlled and a physical page number is added and printed. A field 1202 denotes physical page setting information in which the setting of layout or color/monochrome is stored
15 when the layout or the color/monochrome can be designated for each physical page. A field 1203 designates the number of logical pages allocated to the physical page. If four pages are allocated to one physical page, an ID indicating 4 or a four page
20 printing will be stored. After a field 1204, the information of logical pages of the number designated by the field 1203 is stored. The actual number of page data may be possibly smaller than the number of pages designated by the field 1203 depending on the number of
25 pages printed from the application 201. In order to meet such a case, special data showing a space page is stored in the logical page information.

Fig. 13 shows an example of the physical page setting information indicated by 1202. A field 1301 denotes the arrangement order of logical pages on a physical page in which the designation of an order (transversely from an upper part in a left side, downward from an upper part in a left side, etc.) for arranging the logical pages on a physical page on the basis of the N page printing is stored. The arrangement order may not be applied depending on a system. The logical page information after the field 1204 may be arranged in order in accordance with the arrangement order without using a page number sequence in place of the setting of 1301. A field 1302 indicates the obverse/reverse side information of the duplex side printing which is employed, for example, upon registration of a binding margin in the obverse/reverse side. A field 1303 denotes the designation of color page/monochrome page. In the case of a printer having a monochrome mode and a color mode, the above designation is a value used when the user wishes to print color pages by the color mode and monochrome pages by the monochrome mode in a document with the color pages mixed with the monochrome pages. The provision of this information enables the processes to be changed for each page as an auto-color mode in a color printer. Specifically, in the case of the color page, an intermediate transfer body (an intermediate

transfer drum, an intermediate transfer belt) or a transfer body (a transfer drum, a transfer belt) rotates for several minutes for device color, rotates four times in the case of YMCK, and rotates once only for black in the case of the monochrome page so as to control a transfer process. A field 1304 denotes additional print information used when additional information such as the number of pages, date, etc. is printed in the physical page. Fields may be added to the physical page setting information depending on the function of a system.

Fig. 14 shows one example of the logical page information shown by 1204. A field 1401 designates the ID of a logical page. By using this ID, the intermediate code of the page description file corresponding to the logical page is referred to from the spool file 303. The intermediate code of the logical page may be accessed to by using the ID. A file or a memory pointer may include the intermediate code itself constituting the logical page. A field 1402 indicates a logical page number which is used when the logical page number is printed as additional information or as the auxiliary information of the logical page ID. In the format information of a field 1403, various kinds of setting items which can be designated for each logical page are stored. For instance, the additional print information such as a

page frame and various kinds of setting information designated for each logical page such as enlargement and reduction rate are stored. Further, if necessary, attribute information for the logical page such as color/monochrome information for each logical page can be also stored. On the contrary, a system in which the change of setting for each logical page or the attribute information for each logical page is not required does not need to have the field 1403.

The job output setting file is configured as described above. A job setting file is substantially equally configured to the above, and includes a printing method (single side printing, duplex side printing, binding printing), a print layout (Nup, poster printing), additional information (water mark, date, the addition of a user name), the number of copies and sheet size information as a job, and the arrangement order of logical pages, an obverse/reverse side of the duplex side printing, a color mode, etc. for each physical page.

Further, in Fig. 3, is illustrated an example in which the setting change editor 307 with the setting change function of the job is arranged in addition to the extending system described above. In the present embodiment, the contents of the setting of the job can be changed by changing the job output setting file, because the single job is contained in the job setting

5

10

15

20

25

a change between the contents of the setting first read in step 1501 between the contents of the setting designated at present. When the contents of the setting are changed, the setting change editor 307 advances to step 1505 to generate a new job output setting file, inform the spool file manager of the presence of a change and finish the processes. On the other hand, when the setting change editor decides that the contents of the setting are not changed in step 1505, the setting change editor sends a notice of no change to the spool file manager to finish the processes. As described above, the setting change editor 307 generates the new job output setting file. When an "OK" button is selected on the user interface screen shown in Fig. 18, the new job output setting file becomes effective and the old job output setting file is deleted. Further, upon change in the job setting file of a single job different from that of the job output setting file, the job setting file is not deleted but stored. Further, when a "return to initial state" button is selected on the screen of Fig. 18, the new job output setting file is deleted and the old job output setting file becomes effective to be displayed. In the present embodiment, although the setting change editor 307 is described as a separate module, it may simply form a part of the user interface of the spool file manager 304. A package form, may be provided, in

5

10

15

20

25

5

[Combining Process Flow]

10

15

20

25

5

10

15

25

5

10

15

20

25

embodiment, when the contents of one setting which are to be necessarily set to one print job is designated, a control is always executed so that a setting cancel message is displayed, however, the present invention is not limited thereto. It is to be understood that a control may be performed so that the setting cancel message is displayed when the contents of the settings of a plurality of print jobs to be combined together are examined and the contents of the settings which can be respectively necessarily set to one print job are different between a plurality of print jobs.

In next step 2003, the spool file manager 304 controls to display the user interface (see Fig. 23) on which the user can recognize the contents of the message and select as to whether the print jobs are combined or not and decides whether or not the user instructs the print jobs to be combined.

In step 2003, when the spool file manager 304 decides that the user instructs not to combine the print jobs together, the spool file manager returns to the step 2001 to select the document (print job) again. The spool file manager 304 may further return to the printing flow shown in Fig. 19 from the step 2001 to print a new document or to change the setting of the already printed document and print the document thus obtained again.

In step 2003, when the spool file manager 304

5

10

15

25

printed in accordance with the setting of two copies and one page printing.

In the case where the document A is combined with the document B, the number of copies is reset to one, the part of the document A is set to a four-page printing and the layout information of the document B has the setting of one page printing. As for the number of copies, the setting on a unit for processing the print job (the designation in Fig. 11), that is to say, one setting can be necessarily set to one print job, so that the composed job needs to be unified or reset to a new value. The page layout (layout information) includes the settings to the individual documents and pages, in other words, information held by the physical page information (see 1203 in Fig. 12) and does not need to be unified so that it is printed while the settings of the original documents are maintained.

A reason why the settings are changed or not changed in such a way upon combining the documents will be described below. Generally, there exist a number of kinds of print settings. They are classified into only one print setting which can exist for all the job obtained after the jobs are combined together and the printing settings which can exist in the respective jobs of the composed job and for each page. These print settings are shown in Fig. 26.

Only one setting that the composed job can have indicates a setting significant in stapling for all the job obtained by combining the document A with the document B as in the setting in stapling, however, is not significant in stapling only the part of the document B. In the case where it is desired to simply staple the document A and the document B together and output the stapled documents, the settings of four page printing and one page printing relative to the original documents are desirably stored. In practice, since a setting for printing a plurality of pages on one page is such a setting as to be allocated to the surface of a sheet to be printed, this setting does not need to be arranged for all the jobs upon combining the jobs together. The setting items can be located in mixture after the jobs are joined together.

The recognition message in the step 2003 asks the user to recognize the setting items to be present in mixture or the setting items whose settings are unified in a system in which the settings can be provided in mixture even after the combination of the jobs. Fig 23 described above presents to the user only items whose settings are unified. Since there exist actually a number of setting items, the recognition message may represent representative items as shown in Fig. 23 with good maneuverability instead of listing up all the items.

Fig. 29 is a view for explaining the logical structure of the intermediate file in which are roughly stored the setting information part of the print job and the data of each page of the job. The setting information part of the print job corresponds to the above described job setting file (SDF) in which not only the information of a structure body called DEVMODE or PDEVICE under a Windows environment, but also all items set by the printing dialog are stored. The data of each page is equivalent to the above described page description file (PDF). Depending on the package of a system, a structure having another substance for each page or a structure in which all data is accommodated in one file as shown in Fig. 29 may be employed. When a plurality of jobs are combined together, the SDF parts of the intermediate files of documents to be combined together are scanned, the contents of the settings are compared with each other and the settings are unified and rounded off.

Next, an internal data structure in the combining process will be described. Fig. 27 shows one example of a data structure (job management list) for managing the jobs listed up on the spool file manager 304. The spool file manager 304 adds the ID of the intermediate file to the job management list every time the intermediate file is spooled. As for the ID of the intermediate file, information which can specify the

intermediate file from the ID, for example, are used as the ID a file name if the intermediate file is located in a file system, a pointer if the intermediate file is present in a memory, and so on.

5 Fig. 28 shows one example of the job management list when the spool file manager 304 manages the composed jobs. In this example, in order to discriminate the composed job from ordinary job, a pair of a job ID and a flag for indicating whether or not
10 the job is a composed job represents one job. When the flag shows the ordinary or regular job, the ID of the intermediate file is stored. When the flag shows the composed job, the ID of the composed job is stored.

15 In this case, since the composed job is managed in the memory, a pointer to a structure body which represents the composed job is stored. The structure body representing the composed job comprises the number of jobs in the composed job and the ID of the
20 intermediate file of each print job in the composed job. In such a way, the intermediate file in which the data is actually stored is not directly operated but a logical value of the Job ID is operated, so that resources necessary for a job operation can be saved. Further, even when the jobs are repeatedly combined
25 together, the structures of the files are maintained, and therefore, the jobs can be reset to their states when they are spooled.

00707 68E66960

Fig. 32 is a flowchart showing job operation processes in the spooler 302 and the spool file manager 304.

In step 3201, the spooler 302 or the spool file
5 manager 304 first receives a notice or print start
notice from the user.

In step 3202, the spooler 302 decides whether or not the received notice is the job print notice of a store setting. In the step 3202, when the spool file manager 304 decides that the received notice is the print start notice of the store setting, the spool file manager 304 advances to step 3203 to register the intermediate file ID of the noticed print job in the job management list held by itself and return to the step 3201 in order to receive a next notice.

In the step 3202, when the spool file manager 304 decides that the received notice is not the job print start notice of the store setting, the spool file manager advances to step 3204 to decide whether or not the received notice is an instruction notice for combining the jobs together illustrated in Fig. 16. When the received notice is the instruction notice for joining the jobs together, the spool file manager 304 advances to step 3205 to prepare a composed job structure for managing the composed jobs by using the setting change editor 307.

Then, the spool file manager 304 advances to step

```

5      to delete the jobs copied to the composed job structure
      from the job management list held by itself and add a
      composed job structure newly prepared in the step 3205
      to the job management list. Then, the spool file
      manager 304 returns to the step 3201 to wait for a next
10     input.

```

In the step 3204, when the received notice is not an instruction for combination of the jobs, the spool file manager 304 further advances to step 3208 to decide whether or not the received notice is an instruction to delete the jobs. When the notice is the instruction to delete the jobs, the spool file manager 304 advances to step 3209 to decide whether a job instructed to be deleted is a composed job or an ordinary job. Here, when the spool file manager decides that the job is the composed job, the spool file manager 304 advances to step 3210 to delete the composed job structure located at the end of the pointer which is registered in the job management list, and moves to step 3211 to delete the job instructed to be deleted from the job management list.

In the step 3209, when the spool file manager 304 decides that the job instructed to be deleted is not a

5

25

Then, the spool file manager 304 returns again to the step 3201 to wait for a next input. In the step 3212, the spool file manager 304 decides that the received notice is not the instruction to duplicate the job, the spool file manager 304 advances to step 3214 to decide whether or not the notice is an instruction to decompose the job. When the spool file manager 304 decides that the notice is the instruction to decompose the job, the spool file manager 304 proceeds to step 3215 to return all the job IDs held in the composed job structure indicated by the job pointer of the job to be decomposed to the job management list, delete the job to be decomposed from the job management list and also delete the composed job structure. Then, the spool file manager 304 displays the job icon of the single job on the user interface screen illustrated in Fig. 16.

Further, before moving to step 3215, a message for recognizing whether the composed job is to be truly decomposed may be displayed as illustrated in Fig. 25. Then, the spool file manager 304 returns again to the step 3201 to wait for a next input.

Now, the operation of the composed job will be described below. The data structure used upon preview of the print process of the composed job is managed by

5

10

15

20

25

5
10

15

20

25

Then, the spool file manager 304 advances to step 3302 to decide whether or not the input from the user is a request to delete a job. When the spool file manager 304 decides that the input from the user is the deletion request for the job, the spool file manager 304 advances to step 3303 to decide whether or not the

5

10

25

the user is an instruction to rearrange the job order. In the step 3305, when the spool file manager 304 decides that the input from the user is the instruction to rearrange the job order, the spool file manager advances to step 3306 to replace the ID of the job to be moved which is currently selected by the ID of a job to which the former moves. Fig. 31A shows an example in which the second job is moved to the first position in accordance with a change of the data structure upon change of the job order. The job ID held in the position of the first job of the composed job is replaced by the job ID held in the position of the second job, so that the order change of the jobs can be realized. In the step 3305, when the spool file manager decides that the input from the user is not the instruction to rearrange the job order, the spool file manager 304 performs a process in accordance with other instructions to return to the step 3301.

Now, an operation for each page will be described hereinafter. The page can be deleted for each logical page in accordance with a control process indicated by 3004 in Fig. 30. In this case, the physical page information file is operated. Since the preview is displayed in 3005 of Fig. 30, the physical page information file is already prepared from the job management list.

Fig. 34 is a flowchart for explaining a process

5

10

15

25

examples of the special processes in the job boundary are enumerated as described below. In the case of the duplex printing, when the last page of the job A is printed on the front surface, if it can be set whether or not the first page of the subsequent job B is printed on the back side of the sheet, any print is not performed on the back side of the last page so that the first page is printed on the front surface of a next sheet depending on the setting, the first page of the job B is successively printed on the back surface, or the physical page information file is configured to be divided.

In the step 3406, when the spool file manager 304 decides that the page is located in the job boundary, the spool file manager 304 advances to step 3407 to perform the process of the job boundary and moves to step 3408. In the step 3406, the spool file manager decides that the page is not a job boundary page, the spool file manager 304 advances to the step 3408. In the step 3408, the spool file manager 304 shifts a page subsequent to the logical page to be processed so as to fill an unoccupied page with the page. Then, the spool file manager 304 advances to step 3409 to move backward the logical page to be processed by one and returns to the step 3403. As a result of the successive repetitions, when the processes advance to the last page of the composed job, the spool file manager 304

5

10

15

20

25

to be combined together so as to obtain one composed job, and generating print setting information for the composed job in which information that can be respectively merely set to one print job is unified.

5 Therefore, a plurality of print jobs respectively having the print setting information can be joined together. Further, the inconvenience in the print setting upon joining the print jobs together can be eliminated.

10 Further, since the setting unifier further includes a recognizing unit for analyzing the print setting information of a plurality of print jobs to be combined together and recognizing to select whether the settings are unified or the print jobs are not combined
15 together when information which can be respectively set only to one print job is mutually different, the combination or composition of the jobs which is not desired by a user can be avoided.

[Layout Unifying Process]

20 Figs. 35 to 39 respectively roughly show a processing flow for explaining a " layout unifying process" in the spool file manager 304 and the setting change editor 307 which is one feature of the present invention. Figs. 40 to 41 respectively show examples
25 of the setting change editor 307. The summary of the present invention will be described by using the above described means.

As described above, when a plurality of print jobs are stored on the spool file manager 304, the list of the print jobs are displayed as illustrated in Fig. 16 so that the spool file manager 304 waits for an operation instruction. Then, when a plurality of jobs are selected from the list and a combining instruction set to the menu or the icon is supplied, it is decided in a deciding step S3501 for deciding whether or the combining instruction is supplied that the combining instruction is supplied. Then, the setting change editor 307 as shown in Fig. 18 is started in the start step S3502 of the setting change editor 307. Then, as described above, the job output setting files (see Figs. 10 to 14) are generated. Thus, while the print jobs spooled in the intermediate files are listed up and displayed as shown in Fig. 16, when a plurality of print jobs are selected and the instruction of "combination of jobs" is supplied, the instructed print jobs are simply sequentially combined together from an upper part. In other words, the page layout information for each physical page of the composed job is prepared in the job output setting file on the basis of the job setting files (including the page layout information) of the respective single jobs.

Then, in order to display a print setting tab and the preview shown in Fig. 18, a next initial layout setting obtaining step S3503 is performed. Here, the

layout indicates what number of logical pages are assigned to one physical page and how the logical pages are arranged. For instance, if one logical page is assigned to one physical page, 1 up is used as a terminology, and when two logical pages are assigned to one physical page, 2 up is used as terminology. The initial layout setting obtaining process is carried out in order to determine the initial layout upon combining the jobs together. As the initial layout, the layouts in which the respective print jobs are held as they are may be utilized or a layout which is unified on the basis of a prescribed rule may be utilized.

As the prescribed rule, there may be considered various rules that the initial layout needs to meet the print job first selected on the spool file manager 304, to meet the print job located at the first position on the list, to meet most of the layouts of a plurality of print jobs, to meet a layout predetermined as a setting of default, etc. In this case, the layout unified on the basis of the prescribed rule is not employed as the initial layout, but the layout in which the respective print jobs are held as they are is adopted. Since the layout information can be provided for each physical page in the job output setting file, the page layout information of the original jobs can be provided as described above and the page layout information of the jobs before the combination thereof can be effectively

preview with a plurality of layouts mixed is obtained. Besides, even when a large preview is displayed, the preview in which a plurality of layouts are mixed likewise is displayed.

5 Now, for preparing the layout, the detail of the
preparing step S3505 of the physical page information
file will be described by way of Figs. 37 and 38.

Initially, the calculating process 3701 of the number of all the physical pages is carried out. This is a process for calculating how many physical pages the composed job has. Here, since the layouts of the jobs before joined are held, the number of jobs is equal to the number of all the physical pages of the jobs to be combined together. Then, the calculating process 3702 of the physical page information is performed. This is a process for preparing the physical page information of each job which constitutes the composed job. The detail of the process is shown in Fig. 38.

20 In the calculating process of the physical page
information, a calculating process 3801 (see Fig. 38)
for calculating the number of the logical pages
allocated to the physical page is first executed. This
is a process for calculating the number of logical
25 pages allocated to each physical page. In the case of
the first physical page shown in Fig. 40, 1 equal to
the number of jobs before combined together is

calculated. Then, a calculating process 3802 of the logical page information is carried out. This is a process for calculating each logical page information indicating the physical page which is a process for calculating the information as shown in Fig. 14. Since the layouts of the jobs before combined together are held in the job output setting file of the composed job, the logical page information is the same as the logical page information of the original job corresponding to the physical page. In the case where the layouts are unified, the logical page information is based on one layout after the unification of the layouts. Then, a deciding process 3803 for deciding whether or not the logical page is the last and an increment process 3804 of a logical page counter are carried out, so that the logical page information corresponding to the number of logical pages which is previously calculated is obtained. Then, a calculating process 3805 of the physical page setting information is performed. This is a process for calculating the physical page setting information shown in Fig. 13. The detail of the calculating process will be shown in Fig. 39.

In the obtaining process 3805 of the physical page setting information, a deciding process 3901 (see fig. 39) for deciding whether the duplex side printing is performed is first carried out. This is a process for

5
10
15
20
25

Then, the processes return to those of Fig. 37 to calculate the physical page information corresponding

5 The physical page information file is prepared and
the layout is formed in accordance with a series of the
above described processes.

10

15

25

instruction to unify the layouts. Then, an obtaining
process 3602 for setting a page layout, an arrangement
order, and an intrusion. The initialization thereof is
obtained in accordance with a predetermined rule. This
5 rule may include various kinds of rules. For instance,
the layout is adapted to meet the layout of the
initially selected print job on the spool file manager
304, to meet that of the first print job on the list,
to meet most of the layouts of a plurality of print
10 jobs, to meet the layout predetermined as the setting
of a default, etc. Here, it is assumed that the layout
is adapted to meet the layout predetermined as the
setting of a default, and, in the layout of 4up, from
an upper part in the left side to the right, the
15 intrusion of the jobs is determined to be permitted.
As for the intrusion of the jobs (page shifting
process), for instance, in the case where the number of
logical pages is 3 in the layout of 4-up, the logical
page equivalent to one remaining page can be compactly
20 shifted. In this case, can be performed a selection
for deciding whether the first logical page of a next
job is laid out on the last of the physical page
(intrusion designation), the first logical page is laid
out on the first of another physical page (designation
25 without intrusion) or the first logical page is laid
out on the first of the back side (intrusion
designation on reverse side).

Then, an editing process 3603 of the physical page information file is carried out to the setting mentioned above. This is a process for editing the physical page information files shown in Figs. 10 to 14 according to the determined layout. This process will be described later in more detail. A next preview process 3604 is carried out on the basis of the physical page information files edited in the above process. This is a process for displaying the preview part shown in fig. 18. Here, since the layout of 4 up from the upper part in the left side to the right in which the intrusion of the jobs is permitted is adopted, the composed job is formed and displayed as illustrated in Fig. 41. On the job output setting file, "4" is designated as the number n of the logical pages allocated to all the physical pages of the physical page information (see 1203 of Fig. 12).

Now, in connection with the formation of the layout, the detail of the editing process 3603 of the physical page information file concerning the job output setting file will be described below.

The calculating process 3701 for calculating the number of all the physical pages. This is a process for calculating again how many physical pages the composed job has in accordance with the designation of "unify layout" of the composed job. If the setting is such a setting as to permit the intrusion of the jobs,

the number of physical pages will be changed.

Considering the examples of figs. 40 to 41, 2 physical pages are obtained. Then, the calculating process 3702 for calculating the physical page information is carried out. This is a process for preparing each physical page information forming the composed job and the detail thereof is shown in Fig. 22.

In the calculating process 3702 of the physical page information, the calculating process 3801 (see fig. 38) for calculating the number of logical pages allocated to the physical page is first carried out. This is a process for calculating the number of logical pages allocated to each physical page. In the case of the first physical page shown in Fig. 41, a prescribed value, or "4" is calculated in the present embodiment by unifying the layouts. As described above, the number of logical pages allocated to the physical page may be determined on the basis of the layout information of the first single job of the composed job. In this case, since the job 1 is designated by "1", the number of logical pages is "1".

Then, a calculating process 3802 of the logical page information is carried out. This is a process for calculating each logical page information indicating the physical page which is a process for calculating the information as shown in fig. 14. Then, a deciding process 3803 for deciding whether or not the logical

5

15

25

Then, a deciding process 3903 for deciding whether or not the print setting is a color printing is performed. This is a process for deciding whether the print setting is the color printing or a monochrome printing. Here, when it is decided that the print setting is the color printing, a next color/monochrome writing process 3904 is carried out. This is a process for deciding whether or not the logical pages to be printed in color are included in the physical page.

When the logical pages to be printed in color are included, color data is written, and when the logical pages are not included, monochrome data is written. Also in this case, the color pages included in the physical page may be possible changed by unification of the layout. Here, the monochrome printing is supposed to be executed, so that the monochrome data is not written.

In such a way, the physical page setting information is generated and obtained. The job output setting file including the physical page setting information thus generated is formed by copying the original job output setting file before the layouts are unified and writing the physical page setting information in the job output setting file thus formed.

Thus, when a "return to initial state" button is pushed down on the user interface for editing the jobs (shown in Fig. 18 or Fig. 40), the contents of the job output

setting file can be returned to those of the job output
setting file before the layouts are instructed to be
unified. Further, in the user interface for editing
the jobs, when an "OK" button is pushed down, a
5 duplicated and updated job output setting file is
overwritten on the original job output setting file, so
that the contents of the job output setting file before
the layouts are unified are erased. In this case, in
the user interface shown in Fig. 16, when the user
10 selects the composed job and instructs the composed job
to be decomposed, the composed job is decomposed to the
individual single jobs. The respective job setting
files are always held in the spool file 303 for the
single jobs. Therefore, the most primary print setting
15 is unchangeably ensured.

Then, the process returns to that of Fig. 37 to
calculate again the physical page information
corresponding to the number of all the physical pages
previously obtained by the deciding process 3703 for
20 deciding whether or not the physical page is the last
or the increment process 3704 of the physical page
counter

In accordance with a series of processes, the
physical page information file is edited and the layout
25 is regenerated. It is to be understood that the
present invention may be applied to a system comprising
a plurality of devices such as a host computer,

interface devices, a reader, a printer, etc. or an apparatus comprising one device such as a copying machine, a printer, a facsimile equipment, etc.

As described in the above embodiment, since the information processor according to the present invention further comprises the layout unification instructing means for instructing the layout information of the composed job to be unified, and, when an instruction is provided for instructing the layout information to be unified, the layout information of the composed job is unified by all the physical pages, the unified layout information can be provided for the composed job even when a plurality of print jobs having a plurality of layout information are combined together.

Further, the objects of the present invention can be achieved by reading and executing a program code stored in a memory medium in which the program code of software for realizing the above described functions of the embodiment by the use of the computer or a CPU 101 or an MPU) of a system or an apparatus.

In this case, the program code itself read from the memory medium realizes the above described functions of the embodiment and the memory medium in which the program code is stored constitutes the present invention.

As the memory medium for supplying the program

code, may be utilized, for example, a floppy disk, a hard disk, an optical disk, a magneto-optic disk, a CD-ROM, a CD-R, a magnetic tape, non-volatile memory card, a DVD, an MO, a ROM, etc.

5 The program code read by the computer is executed,
so that not only the above described functions of the
embodiment can be achieved, but also a part or all of
the actual processes are executed by the OS (operating
system) operating on the computer on the basis of the
10 instruction of the program code or the like and
accordingly, the above described functions of the
embodiment can be achieved.

Further, after the program code read from the memory medium is written in a memory provided in a function extending board inserted into the computer or a function extending unit connected to the computer, the CPU or the like provided in the function extending board or the function extending unit performs a part or all of the actual processes on the basis of the instruction of the program code, so that the above described functions of the embodiment can be achieved by the processes.

Still further, the objects of the present invention can be also achieved by installing the program code of the software for realizing the functions of the embodiment in the computer (or the CPU and the MPU) of the system of the apparatus and reading

In this case, the program code itself downloaded in the download service of the internet and installed realizes the above mentioned functions of the

Further, in order to the functional processes of the present invention, the program code itself installed in the computer also realizes the present

10 invention. In other words, in the claims of the
present invention, a computer program itself for
realizing the functional processes of the present
invention is also included. A method for supplying the
computer program is not limited to a case in which the
15 computer program is stored in the FD or the CD-ROM,
read by the computer and installed in the computer.
The computer is connected to the home page of the
internet by using the browser of a client computer so
that the computer program itself of the present
20 invention, or a file compressed and having an automatic
installing function is downloaded so that the computer
program itself can be supplied. Further, the program
code constituting the program of the present invention
is divided into a plurality of files and respective
25 files are downloaded from different home pages so that
the computer program itself can be supplied. That is
to say, a WWW server for downloading a program file for

realizing the functional processes of the present invention by the computer to a plurality of users is also included in the claims of the present invention.

Still further, the program of the present invention is encoded, stored in the memory medium such as the FD and the encoded program is supplied to the users, then, key information for decoding the encoded program is downloaded from the home page through the internet by the user who clears prescribed conditions, and the key information is used by the user to execute the encoded program and install the program in the computer.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that invention is not limited to the specific embodiments thereof except as defined in the appended claims.

As mentioned above, the information processor according to the present invention comprises an intermediate code converter for converting data to be printed which is generated by an application into print jobs of an intermediate code format and temporarily storing the print jobs in association with the print setting information of the data to be printed; a composition instructing unit for instructing a plurality of print jobs of the intermediate code format

5 composition instructing unit instructs the plurality of
print jobs to be combined together so as to obtain one
composed job and generating print setting information
for the composed job in which information that can be
respectively merely set to one print job is unified.

10

15

25

Still further, since information for designating

5

10

15

20

25

again the composed job.

Still further, since the information processor according to claim 1, further comprises a job divider for dividing the composed job into a plurality of print jobs before they are joined together, the composed job

can be returned to respective single jobs. Accordingly, the user can easily try to generate the composed job.

Still further, since the information processor further comprises a job duplicating unit for designating the print job or the composed job to prepare the duplication of the designated print job, a duplication can be prepared to control a page when the user desires to include another job in a job.

Still further, since the print job or the composed job further includes a setting initializing unit for returning the data to an initial state upon preparation of the data of the intermediate code format as the base of the job on the basis of the print setting information, the user can stably execute an operation such as editing the job.

Still further, since the information processor further comprises a page editing unit for deleting a page designated relative to a logical page in the print job or the composed job, a job operation can be performed as desired by the user and an operability and a degree of freedom are improved.

5

10

25

Still further, since the composed job generator generates the layout information of the composed job for each physical page on the basis of the layout information of a plurality of print jobs, the layout information can be provided for each physical page.

Still further, since the information processor further comprises a close arrangement instructing unit for instructing the logical pages of each print job to be closely arranged; and the composed job information generator determines to closely arrange the logical pages in the physical pages when a close arrangement is instructed by the close arrangement instructing unit, the arrangement of the logical pages excellent in its variation can be achieved. Accordingly, the print jobs can be prepared with ease as desired by the user.

5

15

1. An information processor for generating printing data to be transmitted to a printer comprising:

a composition instructing unit for instructing a plurality of print jobs corresponding to the different data to be printed to be composed together so as to generate one composed job; and

2. The information processor according to claim 1, wherein said setting unifier further includes a recognizing unit for recognizing to select whether the settings are unified or the print jobs are not composed together when the print setting information of a plurality of print jobs to be composed together is respectively analyzed and the information which can be set only to one print job is mutually different.

5

10

15

20

25

5

10

15

20

25

13. The information processor according to claim

5

13, further comprising:

10

15

25

16. The information processor according to claim

5

10

15

25

5

10

15

25

5

10

15

20

25

25. The method for generating printing data according to claim 24, wherein said setting unifying step further includes a recognizing step of recognizing

5

10

15

20

25

30. The method according to claim 24, further comprising an order controlling step of operating a plurality of print jobs in the composed job to reshuffle the order of the print jobs.

5

31. The method according to claim 24, further comprising a job cancelling step of operating a plurality of print jobs in said composed job to cancel a specific print job.

10

32. The method according to claim 24, further comprising a job dividing step of dividing said composed job into a plurality of print jobs before they are joined together.

15

33. The method according to claim 24, further comprising a job duplicating step of designating said print job or said composed job to prepare the duplication of the designated print job.

20

34. The method according to claim 26, wherein said print job or said composed job further includes a setting initializing step of returning the intermediate code format as the base of the job to an initial state upon preparation of the data on the basis of the print setting information.

25

007E07" 68E66960

5

10

15

20

25

5

10

15

20

25

42. The method according to claim 41, wherein said composed job information generating step unifies the layout information of said composed job to prescribed layout information.

5

43. The method according to claim 41, wherein said composed job information generating step unifies the layout information of said composed job to the layout information of the print job corresponding to a first physical page in said composed job.

10

44. The method according to claim 39, wherein said composed job information generating step counts the number of logical pages of said composed job and determines the arrangement of the logical pages in the physical pages for each physical page on the basis of the layout information.

15

45. The method according to claim 44, further comprising a close arrangement instructing step of instructing the logical pages of each print job to be closely arranged in said composed job, wherein said composed job information generating step determines to closely arrange the logical pages in the physical pages when a close arrangement is instructed by said close arrangement instructing step.

20

25

007E07" 68E6696D

46. The method according to claim 45, wherein
said close arrangement instructing step performs any
one of a close arrangement for closely arranging the
logical pages on the same physical pages, a back side
close arrangement instruction for compactly arranging
the logical pages on back sides when the back sides of
the same physical pages are unoccupied, and no
instruction for a close arrangement by constantly
changing the physical pages when original print jobs
are different.

47. A computer-readable memory medium which
stores a printing data generating program for
generating printing data to be transmitted to a
printer, the program comprising:

a spool program code for converting data to be
printed which is generated by an application into a
print job and temporarily storing the print job;

a composition instructing program code for
instructing a plurality of print jobs corresponding to
the different data to be printed to be composed
together so as to generate one composed job; and

a setting unifying program code for analyzing the
print setting information of a plurality of print jobs
when the composition instructing program code instructs
the plurality of print jobs to be composed together so
as to obtain one composed job, and generating print

setting information for the composed job in which information that can be respectively merely set to one print job is unified.

5 48. The memory medium according to claim 47,
wherein said setting unifying program code further
includes a recognizing step of recognizing to select
whether the settings are unified or the print jobs are
not composed together when the print setting
10 information of a plurality of print jobs to be composed
together is respectively analyzed and the information
which can be set only to one print job is mutually
different.

15 49. The memory medium according to claim 47,
wherein said spool program code converts said data to
be printed into the print job of intermediate code
format and temporarily stores the print job as a page
description file by a page unit.

20 50. The memory medium according to claim 49,
wherein information for designating the page
description files laid out on a physical page is added
to the print setting information of said composed job.

25 51. The memory medium according to claim 47,
herein said print setting information is temporarily

52. The memory medium according to claim 47, further comprising a preview display controlling step of controlling a preview based on the print setting information of said print jobs or said composed job to be displayed.

54. The memory medium according to claim 47,
15 further comprising a job cancelling step of operating a
plurality of print jobs in said composed job to cancel
a specific print job.

56. The memory medium according to claim 47,
25 further comprising a job duplicating step of
designating said print job or said composed job to
prepare the duplication of the designated print job.

57. The memory medium according to claim 49,
wherein said print job or said composed job further
includes a setting initializing step of returning the
intermediate code format as the base of the job to an
5 initial state upon preparation of the data on the basis
of the print setting information.

58. The memory medium according to claim 47,
further comprising a page editing step of cancelling a
10 page designated relative to a logical page in said
print job or said composed job.

59. The memory medium according to claim 49,
further comprising a printing data generating step of
15 generating the printing data to be transmitted to said
printer on the basis of the data of the intermediate
code format which is temporarily stored in said spool
program code.

20 60. The memory medium according to claim 59,
further comprising:

a description instruction generating step of
converting the data of the intermediate code format
temporarily stored in said spool program code into a
25 description instruction which can be interpreted in the
description step of an OS and outputting the converted
data; and

a print instruction allocating step of sending a
print instruction received through the description step
of the OS from said application to said intermediate
data converting step and sending the print instruction
5 received through the description step of the OS from
said description instruction generating step to said
printing data generating step.

61. The memory medium according to claim 60,
10 wherein said description instruction is a GDI function,
and said print instruction is a DDI function and said
printing data is a printer language.

62. The memory medium according to claim 47,
15 further comprising a composed job information
generating step of generating the layout information of
said composed job on the basis of the layout
information of a plurality of print jobs when said
composition instructing step instructs a plurality of
20 print jobs to be composed together so as to have one
composed job.

63. The memory medium according to claim 62,
wherein said composed job information generating step
25 generates the layout information of said composed job
for each physical page on the basis of the layout
information of a plurality of print jobs.

5

10

15

20

25

5

10

20

25

a composition instructing program code for

5 a setting unifying program code for analyzing the
print setting information of a plurality of print jobs
when the composition instructing program code instructs
the plurality of print jobs to be composed together so
as to obtain one composed job, and generating print
setting information for the composed job in which
0 information that can be respectively merely set to one
print job is unified.

72. The printing data generating program according to claim 70, wherein said spool program code converts said data to be printed into the print job of intermediate code format and temporarily stores the print job as a page description file by a page unit.

5

10

15

20

25

78. The printing data generating program according to claim 70, further comprising a job dividing step of dividing said composed job into a plurality of print jobs before they are joined together.

79. The printing data generating program according to claim 70, further comprising a job duplicating step of designating said print job or said composed job to prepare the duplication of the designated print job.

80. The printing data generating program according to claim 72, wherein said print job or said composed job further includes a setting initializing step of returning the intermediate code format as the base of the job to an initial state upon preparation of the data on the basis of the print setting information.

81. The printing data generating program according to claim 70, further comprising a page editing step of cancelling a page designated relative to a logical page in said print job or said composed job.

82. The printing data generating program according to claim 72, further comprising a printing

data generating step of generating the printing data to be transmitted to said printer on the basis of the data of the intermediate code format which is temporarily stored in said spool program code.

5

83. The printing data generating program according to claim 82, further comprising:

10 a description instruction generating step of converting the data of the intermediate code format temporarily stored in said spool program code into a description instruction which can be interpreted in the description step of an OS and outputting the converted data; and

15 a print instruction allocating step of sending a print instruction received through the description step of the OS from said application to said intermediate data converting step and sending the print instruction received through the description step of the OS from said description instruction generating step to said
20 printing data generating step.

84. The printing data generating program according to claim 83, wherein said description instruction is a GDI function, and said print
25 instruction is a DDI function and said printing data is a printer language.

5

10

20

25

information generating step unifies the layout information of said composed job to prescribed layout information.

5 89. The printing data generating program according to claim 87, wherein said composed job information generating step unifies the layout information of said composed job to the layout information of the print job corresponding to a first
10 physical page in said composed job.

 90. The printing data generating program according to claim 75, wherein said composed job information generating step counts the number of
15 logical pages of said composed job and determines the arrangement of the logical pages in the physical pages for each physical page on the basis of the layout information.

20 91. The printing data generating program according to claim 90, further comprising a close arrangement instructing step of instructing the logical pages of each print job to be closely arranged in said composed job, wherein said composed job information
25 generating step determines to closely arrange the logical pages in the physical pages when a close arrangement is instructed by said close arrangement

00699389.103100

instructing step.

92. The printing data generating program
according to claim 91, wherein said close arrangement
5 instructing step performs any one of a close
arrangement for closely arranging the logical pages on
the same physical pages, a back side close arrangement
instruction for compactly arranging the logical pages
on back sides when the back sides of the same physical
10 pages are unoccupied, and no instruction for a close
arrangement by constantly changing the physical pages
when original print jobs are different.

001507 08060960

In order to compose a plurality of print jobs together to prepare one composed job and provide a desired printed result with no inconvenience to a user, an information processor of the present invention includes a generator for generating print setting information for the composed job, for analyzing the print setting information of a plurality of print jobs and unifying information which can be respectively set only to one print job when a plurality of print jobs are instructed to be composed together so as to obtain one composed job.

FIG. 1




FIG. 2




FIG. 3





FIG. 4



START




FIG. 6




FIG. 7




FIG. 8

?

x

GENERAL

DETAIL


MAIN

PAPER

LAYOUT

DEVICE OPTION

OVERLAY




PAPER SIZE:
A4

OUTPUT SIZE:
A4

☐ ENLARGEMENT:

801

PAGE LAYOUT:
2-PAGE PRINTING

 LEFT TO RIGHT

DIRECTION:
☐ A ☒ PORTRAIT

PAPER SUPPLY:
AUTO

☐ A ☐ LANDSCAPE

COPIES:
1

SET DETAIL

RESTORE DEFAULT

OK

CANCEL

ADAPT

HELP

FIG. 9

?

x

GENERAL

DETAIL

PAGE SETUP

FINISH

PAPER SUPPLY

PRINT QUALITY

DEVICE SETUP

FAVORITES:

DEFAULT SETTING

STORE

A

ORIGINAL SIZE:

A

PAPER SIZE:

1

COPIES:

(1~255)

A

DIRECTION:

PORT-

RAIT

A

LAND-SCAPE

1 PAGE/SHEET (DEFAULT)

100

MAGNIFICATION:

% (50~200)

CONFIDENTIAL

EDIT STAMP

RESTORE DEFAULT

A4 (MAGNIFICATION: AUTO)

VERIFY SETTING

USER-DEFINED PAPER

PAGE OPTION

RESTORE DEFAULT

OK

CANCEL

ADAPT

HELP

FIG. 12

PHYSICAL PAGE NO.	1201
PHYSICAL PAGE SETTING INFO	1202
N: NO. OF LOGICAL PAGES IN PHYSICAL PAGE	1203
1ST LOGICAL PAGE INFO	1204
2ND LOGICAL PAGE INFO	1205
...	1206
NTH LOGICAL PAGE INFO	1207

FIG. 13

ARRANGEMENT OF LOGICAL PAGES IN PHYSICAL PAGE	1301
OBVERSE/REVERSE SIDE OF DUPLEX PRINT	1302
COLOR/MONOCROME PRINT	1303
ADDITIONAL INFO	1304

FIG. 14

LOGICAL PAGE ID	1401
LOGICAL PAGE NO.	1402
FORMAT INFO	1403


FIG. 15

FIG. 16




FIG. 17




FIG. 18

EDIT JOB

NAME OF COMPOSED JOB

WORD-OFFICE REPORT.PR.DOC

1

2

1

2

DELETE PAGE

PREVIEW

JOB LIST

SET PRINTING

COPIES: 1 (1~255)

SURFACE: SINGLE

☐ STAPLING

☐ CENTER BINDING

☒ UNIFY LAYOUT

PAGE LAYOUT: 1 PAGE/SHEET

ARRANGEMENT:

☐ SET JOB BOUNDARY

SET DETAIL

RETURN TO INITIAL STATE

OK

CANCEL

HELP


FIG. 19

FIG. 20






FIG. 21

DOCUMENT A :
5 COPIES, 4 PAGES



DOCUMENT B :
2 COPIES, 1 PAGE



COMPOSED DOCUMENT : 1 COPY

1 PAGE

4 PAGES




FIG. 22




FIG. 23




FIG. 25




FIG. 24




FIG. 26

SETTING	EXAMPLE
1 FOR 1 COMPOSED JOB	NO. OF COPIES, STAPLING, ...
SEVERAL IN MIXTURE FOR 1 COMPOSED JOB	LAYOUT (N-UP), PAGE FRAME, WATER MARK, TERMINOLOGY, PAPER SUPPLY PORT

FIG. 27




FIG. 28




FIG. 29




FIG. 31A




FIG. 31B




FIG. 30




FIG. 32





FIG. 33

FIG. 34





FIG. 35


FIG. 36

FIG. 37





FIG. 38

FIG. 40

EDIT JOB

NAME OF COMPOSED JOB

COMPOSED JOB 1

3 SHEETS

1 ①

2 ① 2 ②

2 ③ 2 ④

3 ①

1

2

3

DELETE PAGE

PREVIEW

JOB LIST

SET PRINTING

COPIES: 1 (1 ~ 255)

SURFACE: SINGLE

☐ STAPLING

☐ CENTER BINDING

☒ UNIFY LAYOUT

PAGE LAYOUT: 1 PAGE / SHEET

ARRANGEMENT:

PAGE SHIFTING:

SET DETAIL

RETURN TO INITIAL STATE

OK

CANCEL

HELP

FIG. 41

EDIT JOB

NAME OF COMPOSED JOB

COMPOSED JOB 1

2 SHEETS

1 ① 2 ①

2 ② 2 ③

2 ④ 3 ①

1

2

DELETE PAGE

PREVIEW

JOB LIST

SET PRINTING

COPIES : 1 (1~255)

SURFACE : SINGLE

☐ STAPLING

☐ CENTER BINDING

☒ UNIFY LAYOUT

PAGE LAYOUT : PAGE SHEET

ARRANGEMENT : FROM LEFT, TOP TO RIGHT

☒ PAGE SHIFTING : YES

SET DETAIL

RETURN TO INITIAL STATE

OK

CANCEL

HELP